


Product technical sheet

NETTIX 1610









4 - 14 years

3 kids

20,3 m²

Material specification

- Hot-dip galvanized and powder coated or powder galvanized and powder coated construction of 100 x 100 mm profile,
- Platforms made of durable anti-slip and waterproof HPL plate,
- Steel ropes in polypropylene braid, connected with durable plastic elements, stainless steel or aluminum,
- Calibrated stainless steel chains, preventing fingers entrapment,
- Stainless steel screws and/or screws covered with plastic caps,
- Safe end caps made of polypropylene,



Physical development




balance





passage











Product technical sheet

NETTIX 1610

Product data

Length	336 cm	
Width	50 cm	
Total height	223 cm	
Age group	4 - 14 years	
Number of users	3 kids	
Safety zone	20,3 m2	
Free fall height	100 cm	
In accordance with norm EN	1176-1:2017+A1:2023	
Weight of the heaviest part	27 kg	
Dimensions of the largest part	300x10x10 cm	
Availability of spare parts	YES	
Installation time	3 h	
Color options		

Data is subject to change without prior notice.

Additional information

- equipment intended for public playgrounds;
- equipment has a certificate issued by an accredited entity or a declaration of conformity;
- no sharp edges or chinks that would pose a danger of jamming the head, fingers or any other body parts;
- anchoring on flat surface, 80/70 cm deep;
- render is for reference only, the actual appearance of the equipment and its color may vary;

Guarantee



30 year guarantee -Durability of steel and 15 stainless steel structural elements



15 year guarantee - Durability of steel and stainless steel structures of mobile devices; durability of Robinia wood structural elements



10 year guarantee - Structural strength of HDPE, 100% recycled HDPE and HPL elements; structural elements made of 100% recycled material (composite)



5 year guarantee - Corrosion resistance of stainless steel and hot-dip galvanized and powder-coated steel elements, resistance to bark beetles and rotting of wooden structural elements

Detailed information in the guarantee card



VAT: 534-250-14-46 PHONE: +48 42 203 24 99 ext. 26 M: +48 793 404 991





Surfaces according to EN 1176-1:2017+A1:2023

	Description (mm)	Layer thickness (cm)	Maximum fall heights (cm)
Turf/ top layer of soil (A,B,C)	-	-	≤100
hark (A.C.)	Particle size from 20 to 80	30	≤200
bark (A,C)		40	≤300
woodchips (A,C)	Particle size from 5 to 30	30	≤200
		40	≤300
sand or gravel (A,C)	Particle size from 0,25 to 8	30	≤200
		40	≤300
synthetic attested (A,B,C)	Tested according to EN 1177		100

Product technical sheet

NETTIX 1610

Amount of safe surface corresponding with free fall height:

HIC 100 20,3 m²

Data is subject to change without prior notice.

