



Product technical sheet

JUNGLE 3203







3 - 14 years

19 kids 32,4 m²



Material specification

- Powder galvanized and powder coated or stainless steel construction of 80 x 80 mm profile,
- Platforms, climbing walls and steps made of durable anti-slip and waterproof HPL plate,
- Roofs and side panels made of durable HDPE plate, resistant to weather conditions,
- Slides made of stainless steel with durable HDPE side panels,
- Maze windows made of polycarbonate, balls made of synthetic material,
- Durable climbing stones made of polyester resin composite with mineral fillers,
- Steel ropes in polypropylene braid, connected with durable plastic elements, stainless steel or aluminum,
- Stainless steel bars,
- Stainless steel screws and/or screws covered with plastic caps,
- Safe end caps on top of the structure made of rubber or polypropylene,



Facilitating disability



easy access



integration



Intellectual development



manipulation



thinking



Physical development



sliding



climbing

M: +48 793 404 991

















number of activity elements



stairs

730 390 HIC 200 061 16,9 m² HIC 90 190 305 999 HIC < 60 HIC 120 3,2 m² 3,8 m² HIC < 60 HIC 100 200





Product technical sheet

JUNGLE 3203

Product data

| Length | 390 cm | |
|--------------------------------|---------------------|--|
| Width | 305 cm | |
| Total height | 350 cm | |
| Age group | 3 - 14 years | |
| Number of users | 19 kids | |
| Safety zone | 32,4 m2 | |
| Free fall height | 200 cm | |
| The height of the platforms | 40, 90, 120 cm | |
| slide platform height | 90 cm | |
| In accordance with norm EN | 1176-1:2017+A1:2023 | |
| Weight of the heaviest part | 19 kg | |
| Dimensions of the largest part | 8x8x394 cm | |
| Availability of spare parts | YES | |
| Installation time | 7 h | |
| Color options | 6 • | |
| | | |

Data is subject to change without prior notice.

Additional information

- equipment adapted for the disabled; intended for public playgrounds;
- equipment has a certificate issued by an accredited entity or a declaration of conformity;
- no sharp edges or chinks that would pose a danger of jamming the head, fingers or any other body parts;
- anchoring on flat surface, 80/70/60 cm deep;
- slide should not be installed southwards;
- render is for reference only, the actual appearance of the equipment and its color may vary;

Guarantee



30 year guarantee -Durability of steel and 15 stainless steel structural elements

[SS] 32,4 m²



15 year guarantee - Durability of steel and stainless steel structures of mobile devices; durability of Robinia wood structural elements



10 year guarantee - Structural strength of HDPE, 100% recycled HDPE and HPL elements; structural elements made of 100% recycled material (composite)



5 year guarantee - Corrosion resistance of stainless steel and hot-dip galvanized and powder-coated steel elements, resistance to bark beetles and rotting of wooden structural elements

Detailed information in the guarantee card

Vinci Group Sp. z o.o. Seminaryjna 9 Street 99-400 Łowicz

VAT: 534-250-14-46 PHONE: +48 42 203 24 99 ext. 26 M: +48 793 404 991



biuro@vinci-play.com info@vinci-play.com www.vinci-play.com



Surfaces according to EN 1176-1:2017+A1:2023

| | Description (mm) | Layer thickness (cm) | Maximum fall heights (cm) |
|---------------------------------|---------------------------------|-------------------------|------------------------------|
| Turf/ top layer of soil (A,B,C) | - | - | ≤100 |
| bark (A,C) | Particle size from 20 to 80 | 30 | ≤200 |
| | | 40 | ≤300 |
| woodchips (A,C) | Particle size from 5 to 30 | 30 | ≤200 |
| | | 40 | ≤300 |
| sand or gravel (A,C) | Particle size from 0,25 to 8 | 30 | ≤200 |
| | | 40 | ≤300 |
| synthetic attested (A,B,C) | Tested according to EN 1177 | | 200 |

Product technical sheet

JUNGLE 3203

Amount of safe surface corresponding with free fall height:

| HIC <60 | 3,2 m ² |
|---------|--------------------|
| HIC 90 | 3,4 m ² |
| HIC 100 | 5,1 m ² |
| HIC 120 | 3,8 m² |
| HIC 200 | 16,9 m² |

Data is subject to change without prior notice.

