



Product technical sheet

MAXX 2902







4 - 14 years

30 kids

76,9 m²



Material specification

- Hot-dip galvanized and powder coated steel construction with a diameter of 160
- Hot-dip galvanized and powder coated steel construction with a diameter of 220 mm,
- Platforms made of durable anti-slip and waterproof HPL plate,
- Side panels made of durable HPL plate, resistant to weather conditions,
- Covers made of stainless steel,
- Stainless steel tube slide,
- Elements made of safe, certified rubber with textile reinforcement,
- Steel ropes in polypropylene braid, connected with durable plastic elements, stainless steel or aluminum,
- Calibrated stainless steel chains, preventing fingers entrapment,
- Stainless steel bars,
- Stainless steel screws and/or screws covered with plastic caps,



Physical development



balance

sliding

climbing



hiding



community



12/02/2025






















Product technical sheet

MAXX 2902

Product data

Length	905 cm
Width	515 cm
Total height	1150 cm
Age group	4 - 14 years
Number of users	30 kids
Safety zone	76,9 m2
Free fall height	100 cm
The height of the platforms	890 cm
tube slide platform height	890 cm
In accordance with norm EN	1176-1:2017+A1:2023
Availability of spare parts	YES

Data is subject to change without prior notice.

Additional information

- equipment intended for public playgrounds;
- equipment has a certificate issued by an accredited entity or a declaration of conformity;
- no sharp edges or chinks that would pose a danger of jamming the head, fingers or any other body parts;
- slide should not be installed southwards;
- render is for reference only, the actual appearance of the equipment and its color may vary;

Guarantee



30 year guarantee -Durability of steel and 15 stainless steel structural elements



15 year guarantee - Durability of steel and stainless steel structures of mobile devices; durability of Robinia wood structural elements



10 year guarantee - Structural strength of HDPE, 100% recycled HDPE and HPL elements; structural elements made of 100% recycled material (composite)



5 year guarantee - Corrosion resistance of stainless steel and hot-dip galvanized and powder-coated steel elements, resistance to bark beetles and rotting of wooden structural elements

Detailed information in the guarantee card



VAT: 534-250-14-46 PHONE: +48 42 203 24 99 ext. 26

M: +48 793 404 991





Surfaces according to EN 1176-1:2017+A1:2023

	Description (mm)	Layer thickness (cm)	Maximum fall heights (cm)
Turf/ top layer of soil (A,B,C)		-	≤100
bark (A,C)	Particle size from 20 to 80	30	≤200
		40	≤300
woodchips (A,C)	Particle size from 5 to 30	30	≤200
		40	≤300
sand or gravel (A,C)	Particle size from 0,25 to 8	30	≤200
		40	≤300
synthetic attested (A,B,C)	Tested according to EN 1177		100

Product technical sheet

MAXX 2902

Amount of safe surface corresponding with free fall height:

HIC <60	44,7 m ²
HIC 100	32,2 m ²

Data is subject to change without prior notice.

