Unit Specification		
Equipment Dimensions	0.58m x 0.35m x 0.70m	FHF
	0.6m	
Overall Weight	20.0kg	Heaviest Part
	12.4kg	
Largest Part	0.22m x 0.33m x 0.45m	Longest Part
	0.45m	
Concrete Required	$0.16m^3$	Construction Space
	1.5m x 1.5m x 1.8m	
Manpower Required	1	Estimated Time
	3	

Bolt length measured as diagram.

Copyright © Playdale Playgrounds Ltd 2022. All rights reserved.

Components

Common Parts List			
Part	**Qty**	**Image**	**Description**
SPR209	1*		Snail Springer CGL Middle
SPR210	1*		Snail Springer CGL Bottom
SPR211	1*		Snail Springer CGL Head
SPR212	1*		Snail Springer CGL Shell
SPR206	1*		Springer Handle Assembly Black
SPR207	1*		Snail Springer Handle CGL
SPR208	1*		Springer Handle 2 Assembly Black
SPR910	1		Spring 18mm
SPRX2	2		Grey Base Plate Cover
Kitting Pack			
F022	4*		M10 X 55mm S/S Coach Bolt
F110	4*		M10 Washer
F762	2*		M10 X 55mm Security Bolt
F608	2*		City Springer Ball
F804	4		M10 Nylock Dome Nut
F600A	2*		Plastic Counterbore Housing Washer
F797	2*		M4 X 30mm CSK S/S Security Bolt
F798	2*		M4 S/S CSK Barrel Nut

Surface Fixed Additional Parts List			
Part	**Qty**	**Image**	**Description**
SPRX5	2		Surface Fix Plate

Parts marked * may be supplied pre-assembled as SPR#SN(A)

Copyright © Playdale Playgrounds Ltd 2022. All rights reserved.

BS EN 1176 Impact Area

Surfacing Specification	
Finished Gradient	1 in 20 max
Free Height of Fall	0.6m
BS-EN1176 Impact Area	5.60m2
Impact Area Perimeter	8.40m2
Loosefill Area	13.8m2
Loosefill Area Perimeter	13.50m

Copyright © Playdale Playgrounds Ltd 2022. All rights reserved.

Standard Foundation Plan

Minimum Concrete Specification: C16/20 (20 N/mm² min. compressive strength)
Recommended Mix: 1 part cement/ 2 part sand/ 4 part stone.

NOT TO SCALE

Standard Foundation Detail

NOT TO SCALE

NOTE: All holes must taper out from hole width at top of hole (as shown) to give maximum stability. In loose or sandy ground all hole width dimensions should be increase by approximately 50%.

Copyright © Playdale Playgrounds Ltd 2022. All rights reserved.

Surface Fixed Foundation Plan

Concrete Required	**0.16m³**

Nominal Surfacing Depth (s) = 30mm
Allowance 30mm—60mm

Foundations MUST be level, separate foundation MUST be level with each other. (maximum gradient 1 in 500) Minimum Concrete Specification: C20/25 (20 N/mm² min. compressive strength).

Jukebox+ Range: Maximum calculated compressive load [7kN] per foundation and tensile load [2kN] per fixing. Module specific loading figures to assess existing concrete foundations are available on request.

Playdale's surface fix system has been designed for use with an Resin/Adhesive Anchor system using appropriate threaded stud/rod and Anti-Vibration Nut.

Where a concrete slab is preferred over individual plinths/foundations the depth (d) can be significantly reduced.

All Plates and fixings should be covered appropriately as not to cause impact or trip hazard.

NOT TO SCALE

NOTE: All holes must taper out from hole width at top of hole (as shown) to give maximum stability. In loose or sandy ground all hole width dimensions should be increase by approximately 50%.

Copyright © Playdale Playgrounds Ltd 2022. All rights reserved.

01

SPR910	1
SPRX2	2

Copyright © Playdale Playgrounds Ltd 2022. All rights reserved.

02

SPR910	1
SPRX2	2

03

SPR211	1
SPR206	1
SPR208	1

Copyright © Playdale Playgrounds Ltd 2022. All rights reserved.

04

SPR207	1

05

Torque to 20Nm

SPR209	1
SPR210	1
SPR211	1
SPR212	1
F022	4
F110	4
F797	2
F798	2
F804	4
F762	2
F608	2
F600A	2

If pre-assembled, replace 4 nuts on SPR#SN(A) with F804.

Copyright © Playdale Playgrounds Ltd 2022. All rights reserved.

Copyright © Playdale Playgrounds Ltd 2022. All rights reserved.