



Product technical sheet

CLIMBOO WD1462







3 - 14 years

23 kids

33,9 m²



Material specification

- Construction made of the highest quality laminated, impregnated and double coated pine wood 90 x 90 mm without knots, secured from the top with polypropylene plugs,
- Metal anchors made of hot dip galvanized steel, protecting the wood from direct contact with the ground to prevent rot and to extend the product's life,
- Platforms and climbing walls made of durable anti-slip and waterproof plywood or
- Double wall tube passage made of polypropylene,
- Climbing stones made of durable HDPE plate, resistant to weather conditions,
- Steel ropes in polypropylene braid, connected with durable plastic elements, stainless steel or aluminum,
- Ladders made of steel ropes in polypropylene braid and rungs made of synthetic material,
- Calibrated stainless steel chains, preventing fingers entrapment,
- Stainless steel bars and handrails,
- Screws covered with plastic caps and/or stainless steel screws,
- Safe end caps made of polypropylene,



Physical development



balance

passage



pull-up



climbing

crawling

Vinci Group Sp. z o.o. Seminaryjna 9 Street 99-400 Łowicz


VAT: 534-250-14-46 PHONE: +48 42 203 24 99 ext. 26 M: +48 793 404 991

















Product technical sheet

CLIMBOO WD1462

Product data

Length	240 cm	
Width	233 cm	
Total height	230 cm	
Age group	3 - 14 years	
Number of users	23 kids	
Safety zone	33,9 m2	
Free fall height	220 cm	
The height of the platforms	120 cm	
In accordance with norm EN	1176-1:2017	
Weight of the heaviest part	30 kg	
Dimensions of the largest part	220x9x9 cm	
Availability of spare parts	YES	
Installation time	10 h	
Color options		

Data is subject to change without prior notice.

Additional information

- equipment intended for public playgrounds;
- equipment has a certificate issued by an accredited entity or a declaration of conformity;
- no sharp edges or chinks that would pose a danger of jimming the head, fingers or any other body parts;
- anchoring on flat surface, 80/70/60 cm deep;
- render is for reference only, the actual appearance of the equipment and its color may vary;

Guarantee



30 year guarantee -Structural strength of steel and stainless steel components



15 year guarantee -Structural failure of steel and stainless steel, for dynamic equipment



10 year guarantee - Structural failure of high density polyethylene and high pressure laminates components



5 year guarantee - Corrosion of stainless steel and hot dip galvanized and powder coated components; against bark beetles and rot in case of wooden structural elements

Detailed information in the guarantee card



VAT: 534-250-14-46 PHONE: +48 42 203 24 99 ext. 26 M: +48 793 404 991





Surfaces according to EN 1176-1:2017

	Description (mm)	Layer thickness (cm)	Maximum fall heights (cm)
Turf/ top layer of soil (A,B,C)	-	-	≤100
bark (A,C) Particle size from 20 to 80	30	≤200	
	to 80	40	≤300
woodchips (A,C) Particle size from 5 to 30	30	≤200	
	to 30	40	≤300
sand or gravel (A,C)	Particle size from	30	≤200
	0,25 to 8	40	≤300
synthetic attested (A,B,C)	Tested according to EN 1177		220

Product technical sheet

CLIMBOO WD1462

Amount of safe surface corresponding with free fall height:

HIC <60	0,1 m ²
HIC 165	0,2 m ²
HIC 205	2,1 m²
HIC 220	31,5 m²

Data is subject to change without prior notice.

