



Material specification

- The structure is made of a durable, moisture-resistant and low-temperature recycled composite,
- Platforms and steps made of durable anti-slip and waterproof plywood or HPL plate,
- Structure for platforms made of hot-dip galvanized and powder coated steel;
- Roofs and side palels made of recycled HDPE boards, resistant to weather conditions.
- Slides made of stainless steel with sides made of recycled HDPE boards, resistant to amospheric conditions,
- Handling panels made of recycled HDPE panel, resistant to weather conditions,
- Stainless steel bars,
- · Screws covered with plastic caps and/or stainless steel screws,

Product technical sheet

WOODEN WD1434







1 - 8 years

years 7 kids

19,5 m²





Facilitating disability



easy access



integration



Intellectual development



manipulation



thinking



Physical development



sliding











Product technical sheet

WOODEN WD1434









Product data

Length	215 cm	
Width	145 cm	
Total height	280 cm	
Age group	1 - 8 years	
Number of users	7 kids	
Safety zone	19,5 m2	
Free fall height	90 cm	
The height of the platforms	59, 90 cm	
slide platform height	90 cm	
In accordance with norm EN	1176-1:2017	
Weight of the heaviest part	23 kg	
Dimensions of the largest part	227x9x9 cm	
Availability of spare parts	YES	
Installation time	2,5 h	
Color options		

Data is subject to change without prior notice.

Additional information

- equipment adapted for the disabled; intended for public playgrounds;
- equipment has a certificate issued by an accredited entity or a declaration of conformity;
- no sharp edges or chinks that would pose a danger of jimming the head, fingers or any other body parts;
- anchoring on flat surface, 80/70/60 cm deep;
- slide should not be installed southwards;
- render is for reference only, the actual appearance of the equipment and its color may vary;

Guarantee



30 year guarantee -Structural strength of steel and stainless steel components



15 year guarantee -Structural failure of steel and stainless steel, for dynamic equipment



10 year guarantee - Structural failure of high density polyethylene and high pressure laminates components



5 year guarantee - Corrosion of stainless steel and hot dip galvanized and powder coated components; against bark beetles and rot in case of wooden structural elements

Detailed information in the guarantee card

Vinci Group Sp. z o.o. Seminaryjna 9 Street 99-400 Łowicz VAT: 534-250-14-46 PHONE: +48 42 203 24 99 ext. 26 M: +48 793 404 991





Surfaces according to EN 1176-1:2017

	Description (mm)	Layer thickness (cm)	Maximum fall heights (cm)
Turf/ top layer of soil (A,B,C)	-	-	≤100
bark (A,C)	Particle size from 20 to 80	30	≤200
		40	≤300
Woodchine (A ()	Particle size from 5	30	≤200
	to 30	40	≤300
sand or gravel (A,C)	Particle size from 0,25 to 8	30	≤200
		40	≤300
synthetic attested (A,B,C)	Tested according to EN 1177		100

Product technical sheet

WOODEN WD1434

Amount of safe surface corresponding with free fall height:

HIC 90	11,8 m²
HIC 100	7,7 m ²

Data is subject to change without prior notice.

